



# VA 30 S

## Electric

Article code	Power
800013	230V, 60HZ
706267	400V, 50HZ
800010	480V, 60HZ

Key features	
Wattage/HP	7,5Kw/10HP
Working width	30cm/12"
Distance to wall	9cm/3.5"
Depth hard concrete	6mm/.24"
Depth softer concrete	9mm/.35"
Production/h	50-55m <sup>2</sup> /540sqf
Standard cutters	Octagonal carbide

Physical parameters		
Weight kg/lbs	800013	210/463
	706267	222.8/491
	800010	243/535
Dimensions cm/inch	135×56×109/53×22×43	

Field of application	
<p><b>Depending on the cutter type, hard, brittle to firm or elastic surface materials can be worked e.g.:</b></p> <ul style="list-style-type: none"> <li>• Asphalt and cast asphalt surfaces</li> <li>• Concrete and cement, synthetic stone, floor tiles</li> <li>• Screeds of cement, wood cement, ceramic etc.</li> <li>• Natural stone</li> <li>• Metals</li> <li>• Thermoplastic materials</li> </ul>	
<p><b>Surfaces made of highly elastic soft materials or fabrics and fiber materials cannot be worked, or can only be worked with certain limitations e.g.:</b></p> <ul style="list-style-type: none"> <li>• Latex, rubber, soft plastics and foam materials</li> <li>• Wood, carpets and woven materials</li> </ul>	